

ALL CERAMIC CRYSTAL RESONATORS (SMD)

SMAC-6035



FEATURES

- All ceramic epoxy sealed SMD package
- Wide frequency range
- 2 / 4 pads version available
- 100% Pb-free

Request for samples / quotation

Part number descriptions

Where to buy




Item		Specifications
Nominal Frequency Range	f_0	11.0592.0MHz ~ 40.0MHz (Fundamental)
Frequency Tolerance, $T_a=25^\circ\text{C} \pm 3^\circ\text{C}$	$\Delta f/f$	$\pm 20\text{ppm}$, $\pm 30\text{ppm}$, $\pm 50\text{ppm}$
Load Capacitance	C_L	18pF or customer specify
Frequency Tolerance over Operating Temperature Range	$\Delta f/f$	$\pm 20\text{ppm}$, $\pm 30\text{ppm}$, $\pm 50\text{ppm}$
Operating Temperature Range	T_{OPR}	$-20^\circ\text{C} \sim +70^\circ\text{C}$, $-40^\circ\text{C} \sim +85^\circ\text{C}$
Storage Temperature Range	T_{STG}	$-55^\circ\text{C} \sim +125^\circ\text{C}$
Drive Level	DL	0.1mW (0.5mW Max.)
Shunt Capacitance	C_0	7pF Max.
Insulation Resistance	IR	500M Ω Min.
Aging	Δf_A	$\pm 5\text{ppm/Year}$ Max.

SERIES RESISTANCE (ESR)




Frequency Range	$11.0592 < f_0 \leq 16$	$16 < f_0 \leq 40$
ESR	60 Ω Max.	30 Ω Max.

Please consult our sales representatives for other specifications.

DIMENSION (mm)



SOLDERING PATTERN (mm)



All specifications are subject to change without notice.